



Standart Features

- Steel construction body
- Pneumatic clutch and brake combination
- Adjustable stroke
- Eccentric Crankschaft was made filling
- Liner washer system in connecting rod
- Central lubrication system
- Adjustable rear slides
- 6 guide ram
- Ram adjustment with motor
- Hydraulic overload protection system
- Gear box welded to body
- Gears closed system in oil
- Maint table with T slots
- Additional table with T slots
- Material and scrap groove
- Automatic Reversible Fluid Lubrication System
- Foot paddle
- Double hand control
- Single-continous-interrupted shot - feeding mode options
- PLC applied
- Crank Angle Indicator with Encoder
- 7" Operator Panel
- 3 Color Warning Light
- Security PLC
- Compliance with CE directives
- Safety light curtains
- Press safety valve
- Pneumatic ram balancing cylinders

Optional Features

- Speed Control Unit

	Value	Unit
Capacity	130	Ton
Throat Depth	305	mm
Table - Ram Distance	470	mm
Additional Table - Ram Distance	370	mm
Housing Width	570	mm
Ram Adjusment	90	mm
Press Width	1800	mm
Press Height	2900	mm
Press Depth	1800	mm
Table Hole Diameter	Ø205	mm
Table Depth	610	mm
Table Width	950	mm
Die Tie Hole Diameter	Ø50	mm
Ram Face Size	450 × 750	mm
Table Height From Floor	720	mm
Stroke	10-110	mm
Stroke Per Minute	53	spm
Motor Power	11	kW
Motor Speed	1500	rpm
Weight	7500	kg

A3	ISO 128	HP_130_PK_AEP_HS	Technical Specifications		Page
TASARIM / DESIGNED	Taha Canat	26.12.2022			1/1
ÇİZEN / DRAWN	Taha Canat	20.10.2025			
KONTROL / CHECKED					

HICO MACHINERY AND ENGINEERING LTD. CO. reserves the right to make changes in dimensions without prior notice.