



Standart Features

- Steel construction body
- Pneumatic clutch and brake combination
- Adjustable stroke
- Eccentric Crankschaft was made filling
- Liner washer system in connecting rod
- Central lubrication system
- Adjustable rear slides
- 4 guide ram
- Ram adjustment with ratchet system
- Mechanical disc overload protection system
- Gear box welded to body
- Gears closed system in oil
- Maint table with T slots
- Additional table with T slots
- Material and scrap Groove
- Manuel Hand Pump
- Foot paddle
- Double hand control
- Single-continous-interrupted shot - feeding mode options
- PLC applied
- 7" Operator Panel
- 3 Color Warning Light
- Security PLC
- Compliance with CE directives
- Safety light curtains
- Press safety valve
- Pneumatic ram balancing cylinders

Optional Features

- Electric and Timed Automatic
- Grease Lubrication System
- Speed Control Unit

	Value	Unit
Capacity	100	Ton
Throat Depth	270	mm
Table - Ram Distance	380	mm
Housing Width	440	mm
Ram Adjusment	75	mm
Press Width	1440	mm
Press Height	2540	mm
Press Depth	1540	mm
Table Hole Diameter	Ø175	mm
Table Depth	540	mm
Table Width	750	mm
Die Tie Hole Diameter	Ø45	mm
Ram Face Size	370 × 230	mm
Table Height From Floor	670	mm
Stroke	10-95	mm
Strok Per Minute	56	spm
Motor Power	11	kW
Motor Speed	1500	rpm
Approximate Weight	4050	kg

A3	ISO 128	HP_100_PK_AEP_MS	Technical Specifications		Page
TASARIM / DESIGNED	Taha Canat	08.05.2014			1/1
ÇİZEN / DRAWN	Taha Canat	17.10.2025			
KONTROL / CHECKED					