


Standart Features

- Steel construction body
- Pneumatic clutch and brake combination
- Adjustable stroke
- Eccentric Crankschaft was made filling
- Liner washer system in connecting rod
- Central lubrication system
- Adjustable rear slides
- 4 guide ram
- Ram adjustment with ratchet system
- Mechanical disc overload protection system
- Gear box welded to body
- Gears closed system in oil
- Maint table with T slots
- Additional table with T slots
- Material and scrap Groove
- Manuel Hand Pump
- Foot paddle
- Double hand control
- Single-continious-interrupted shot - feeding mode options
- PLC applied
- 7" Operator Panel
- 3 Color Warning Light
- Security PLC
- Compliance with CE directives
- Safety light curtains
- Press safety valve
- Pneumatic ram balancing cylinders

Optional Features

- Electric and Timed Automatic Grease Lubrication System
- Speed Control Unit

	Value	Unit
Capacity	60	Ton
Throat Depth	250	mm
Table - Ram Distance	320	mm
Additional Table - Ram Distance	235	mm
Housing Width	400	mm
Ram Adjusment	70	mm
Press Width	1380	mm
Press Height	2360	mm
Press Depth	1480	mm
Table Hole Diameter	Ø165	mm
Table Depth	500	mm
Table Width	700	mm
Die Tie Hole Diameter	Ø40	mm
Ram Face Size	345 × 210	mm
Table Height From Floor	660	mm
Stroke	10-85	mm
Strok Per Minute	60	spm
Motor Power	5,5	kW
Motor Speed	1500	rpm
Approximate Weight	3100	kg

A3	ISO 128	HP_60_PK_AEP_MS	Technical Specifications		Page
TASARIM / DESIGNED	Taha Canat	08.05.2014			1/1
ÇİZEN / DRAWN	Taha Canat	17.10.2025			
KONTROL / CHECKED					